

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
26 May 2005 (26.05.2005)

PCT

(10) International Publication Number
WO 2005/048222 A1

(51) International Patent Classification⁷: **G09F 9/30**,
H05B 33/10, 33/14, H01L 29/786, 21/768, 21/288, 27/088

(21) International Application Number:
PCT/JP2004/016798

(22) International Filing Date:
5 November 2004 (05.11.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2003-385965 14 November 2003 (14.11.2003) JP

(71) Applicant (for all designated States except US): SEMI-
CONDUCTOR ENERGY LABORATORY CO., LTD.
[JP/JP]; 398, Hase, Atsugi-shi, Kanagawa 243-0036 (JP).

(72) Inventors; and

(75) Inventors/Applicants (for US only): YAMAZAKI,


Shunpei [JP/JP]; c/o Semiconductor Energy Laboratory Co., Ltd., 398, Hase, Atsugi-shi, Kanagawa 243-0036 (JP). MAEKAWA, Shinji [JP/JP]; c/o Semiconductor Energy Laboratory Co., Ltd., 398, Hase, Atsugi-shi, Kanagawa 243-0036 (JP). NAKAMURA, Osamu [JP/JP]; c/o Semiconductor Energy Laboratory Co., Ltd., 398, Hase, Atsugi-shi, Kanagawa 243-0036 (JP).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH,

[Continued on next page]

(54) Title: LIGHT EMITTING DISPLAY DEVICE, METHOD FOR MANUFACTURING THE SAME, AND TV SET



(57) Abstract: An object of the invention is to provide a display device which can be manufactured with usability of a material improved and with a manufacturing step simplified and to provide a manufacturing technique thereof. One feature of a light emitting display device of the present invention is to comprise a gate electrode formed over a substrate having an insulating surface with a substance having a photocatalytic function therebetween, a gate insulating layer formed over the gate electrode, a semiconductor layer and a first electrode formed over the gate insulating layer, a wiring layer formed over the semiconductor layer, a partition wall covering an edge portion of the first electrode and the wiring layer, an electroluminescent layer over the first electrode, and a second electrode over the electroluminescent layer, wherein the wiring layer covers the edge portion of the first electrode.



GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.